



**Loa âm trần Toa PC 648R** Rated Input 6 W (100 V line), 3 W (70 V line) Rated Impedance 100 V line: 1.7 k $\Omega$  (6 W), 3.3 k $\Omega$  (3 W), 10 k $\Omega$  (1 W) 70 V line: 1.7 k $\Omega$

(3 W), 3.3 k $\Omega$  (1.5 W), 10 k $\Omega$  (0.5 W) Sensitivity 90 dB (1 W, 1 m) (500 - 5,000 Hz, pink noise) Frequency Response 100 - 18,000 Hz (peak -20 dB) Speaker Component 12 cm (5") cone-type Dimensions for Fixing Hole Mounting hole:  $\phi$ 145 $\pm$ 5 mm ( $\phi$ 5.71" $\pm$ 0.2") Ceiling thickness: 5 - 25 mm (0.2" - 0.98") Speaker Mounting Method Spring clamp Finish Baffle: Polypropylene resin, off-white (RAL 9010 or equivalent color)

Grille: Surface-treated steel plate net, off-white (RAL 9010 or equivalent color), paint Dimensions  $\phi$ 168  $\times$  77 (D) mm ( $\phi$ 6.61"  $\times$  3.03") Weight 470 g (1.04 lb) Accessory Paper pattern ...1